

BEOAMP 2

2 x 150W of audiophile sound quality



EFFICIENT AMPLIFIER FOR MULTIZONE INSTALLATIONS

The BeoAmp 2 amplifier is an ultra-compact and powerful audio power amplifier intended for single zone custom installation in modern homes, and can also be used in professional applications. BeoAmp 2 is designed for multiple placement options and fits a 1 unit space in a 19" rack installation as well as table and wall mount possibilities.



BANG & OLUFSEN



Front



Back

SPECIFICATIONS / FEATURES

Amplification

Typical output power
100W per Ch., 8 Ω (1%THD+N, f=1kHz), @ 230Vac

Peak power
150W per Ch., @ 8 Ω
300W per Ch., @ 4 Ω

Placement options

Shelf (Feet included)
19 inch Rack (Rack ears included)
Cabinet

Dimensions/Weight

Height 1.65 inches / 42 mm
Width 7.87 inches / 200 mm
Depth 9.84 inches / 250 mm
Weight 1.9 kg

Connections

Stereo RCA Line in
Stereo RCA Loop out
RJ45 Power Link input
RJ45 Power Link loop out
Phoenix speaker outputs
Mains connector

Standby power consumption

Less than 0.5W

Power supply

Universal Mains 85-264 Vac, 45-65 Hz

Power Management

Audio input sense, 12V trigger and PowerLink

Thermal dissipation

Passive cooling

Colours

Black cabinet

FEATURES

- Ultra-compact enclosure (2 pcs BeoAmp 2 fits in a 1U rack)
- Extremely low weight - up to seven times lighter than similar products
- Up to 2 x 150W channels of audiophile sound quality
- Very low power consumption and heat dissipation thanks to efficient ICEpower Class-D technology
- Comprehensive protection keeps the music playing and your quality costs down
- Removable rack ears and feet are included in the product packaging