

# **BANG & OLUFSEN**





### **SPECIFICATIONS**

Tweeter Dome
Tweeter
Midrange Cone
Midrange Diameter
Woofer Cone
Woofer Diameter
Dimensions grill
Frequency Response
Impedance Minimum

Recommended Amplifier Power

Sensitivity Depth

Cutout Dimension(s)

### **BOP LCR66**

Silk DPSD 1" (25mm)

-

Glass Dual 6 1/2"

7.875" x 15.563" (200 x 395mm)

55Hz-20kHz 6 ohm

25 watts - 150 watts 90dB +/- 3dB 3.75" (95mm)

6.625" x 14.375" (168 x 364mm)

### BOP THTR66

Silk DPSD 1" (25mm) Glass

6.5" (165mm)

Glass

Quad 6 1/2" (165mm)

8.875" x 30.125" (225 x 765mm)

40Hz-20kHz 6 ohm

10 watts - 200 watts 92dB +/- 3dB

3.75" (95mm)

7.87" x 29" (200 x 737mm)

## **FEATURES**

2-way system

Dual-woofer driver gives better bass

EQ Adjustments

X-Wave<sup>™</sup> Woofer Surround Progressive Suspension

Compression Molded Woofer Baskets Spring-lock™ 2.0 tool less installation

Magnetic Grille

True 3-way system

Quad woofer driver gives deep and

power full bass EQ Adjustments

X-Wave™ Woofer Surround Progressive Suspension

Compression Molded Woofer

Spring-lock<sup>™</sup> 2.0 tool less installation

Magnetic Grille